DEUTZ-FAHR 07 D 4007 (1981-1984)



| ENGINE Deutz F3L-912 Capacity: 7,5 liter | | |
|---|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 40 | | |
| Change every 500 hours/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SHPD 15W-40 | Multifleet SCD 30 | |
| Change every 500 hours/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Kroontrak MTH 10W-30 | Multifleet SHPD 10W-40 | |
| Change every 500 hours/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 20W-20 | | |
| Change every 500 hours/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| Change every 500 hours/ 12 months | | |

| TRANSAXLE MANUAL 8/2 Capacity: 16 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Multifleet SHPD 15W-40 | Gearlube GL-4 80W-90 |

DEUTZ-FAHR 07 D 4007 (1981-1984)



| HYDRAULIC SYSTEM Capacity: 14 liter | | | |
|-------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Multifleet SCD 20W-20 | HDX 20W-20 | | |
| 01 1 1001 | 10001 /10 // | | |

Check every 100 hours, change every 1000 hours/ 12 months

| HYDRAULIC BRAKE SYSTEM Capacity: 0,8 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| | | |

Change every 24 months

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| Check every 100 hours | | |

| STEERING BOX Capacity: 0,5 liter | | |
|-------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| 01 1 10 11 110001 | | |

Check every 12 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.