DEUTZ-FAHR 6000 6090 ->14500 (2010-2011)



ENGINE Deutz TCD 2013 L06 4V DCR Capacity: 21 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agrisynth MSP 10W-40

Check every 50 hours, change every 500 hours

DRUM SPEED REDUCER Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
01 1 0501 1 10001	140 (1

Check every 250 hours, change every 1000 hours/ 12 months

use Normal	CLIMATE Moderate
Normal	Modorato
	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 250 hours, change every 1000 hours/12 months

RAPE HEADER Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Change every 12 months		

TRANSMISSION Capacity: 17 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 250 hours, change every 1000 hours/ 12 months	

DEUTZ-FAHR 6000 6090 ->14500 (2010-2011)



renus biosyntii 40	relius II 40	
Perlus Biosynth 46	Perlus H 46	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
HYDRAULIC SYSTEM Capacity: 65 liter		

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	·

AUTOMATIC LUBRICATION SYSTEM		
	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2		
Labora Grease Q5 MP Calcep Grease EP 2		
	PRODUCT RECOMMENDATION 2	

GREASE POINTS/NIPPLES CHAINS COUPLINGS AND GREASE POINTS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP 68	
Change every 50 hours	·

COOLING SYSTEM Capacity: 55 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Change every 24 months	<u> </u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.