

DEUTZ-FAHR AGROLUX AGROLUX 85 - >10001 (2010-2016)



MOTOR Perkins 1000.4-W

Kapacitet: 11 liter, Filterkapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP 10W-40

PRODUKTANBEFALING 2

Agridiesel MSP 15W-40

PRODUKTANBEFALING 3

Agridiesel CRD+ 15W-40

Kontroller alle 10 timer, skift alle 600 timer

ANVEND

Biodiesel B100

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP 10W-40

PRODUKTANBEFALING 2

Agridiesel MSP 15W-40

PRODUKTANBEFALING 3

Agridiesel CRD+ 15W-40

Kontroller alle 10 timer, skift alle 300 timer

DIFFERENTIALE FOR

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Kontroller alle 300 timer, skift alle 1200 timer/ 24 måneder

NAVREDUKTIONER FOR

Kapacitet: 1,5 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Kontroller alle 300 timer, skift alle 1200 timer/ 24 måneder

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 52 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Kontroller alle 50 timer, skift alle 1200 timer/ 24 måneder

DEUTZ-FAHR AGROLUX AGROLUX 85 - >10001 (2010-2016)



HYDRAULISK BREMSESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Kontroller alle 50 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 11 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 10 timer, skift alle 1200 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.