
## **DEUTZ-FAHR AGROLUX AGROLUX F67**





<b>ENGINE</b> Perkins 1000.3-WT Capacity: 7,7 liter, Filter capacity: 1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agridiesel CRD+ 15W-40			
Check every 10 hours, change every 300 hours/ 12 months			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			
Agridiesel CRD+ 15W-40			
Change every 50 hours			

DIFFERENTIAL FRONT Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
0/ / 40/ / 4000	

Check every 10 hours, change every 1200 hours

HUB REDUCTIONS FRONT Capacity: 1,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING
Capacity: 41 liter

USE

CLIMATE

Normal Moderate

PRODUCT RECOMMENDATION 1

Check every 10 hours, change every 1200 hours

**Agrifluid HT** 

## **DEUTZ-FAHR AGROLUX AGROLUX F67**

(2001-2010)



HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2		
Change every 50 hours	<u>'</u>	<u>'</u>	

Change every 50 hours

COOLING SYSTEM Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Charles was 40 hours about a court 4000 hours		

Check every 10 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.