DEUTZ-FAHR AGROPLUS AGROPLUS 70

(1996-2004)



ENGINE Deutz F4L-913 Capacity: 10 liter, Filter capacity: 0,5 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40	

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT (4x4)

Capacity: 6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS FRONT (4x4)

Capacity: 1,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

POWER TAKE OFF FRONT

Capacity: 2,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 30/15

Capacity: 41 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			

Check every 500 hours, change every 24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours		

AIRCONDITIONING COMPRESSOR

Capacity: 1,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

KROON-OIL B.V. Postbus 149 7600 AC Almelo

Dollegoorweg 15 7602 EC Almelo

Telefoon 0546-818165 Verkoop 0546-816184

PRODUCT RECOMMENDATION

DEUTZ-FAHR AGROPLUS AGROPLUS 70

(1996-2004)



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.