

DEUTZ-FAHR AGROTRON MKI AGROTRON

4.95 (1995-1997)

**ENGINE**

Capacity: 10 liter, Filter capacity: 1,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Multifleet SHPD 15W-40***Check every 10 hours, change every 250 hours/ 12 months***DIFFERENTIAL FRONT (4x4)**

Capacity: 4,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 250 hours, change every 1000 hours/ 12 months***HUB REDUCTIONS FRONT (4x4)**

Capacity: 0,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 250 hours, change every 1000 hours/ 12 months***HUB REDUCTIONS REAR**

Capacity: 6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 250 hours, change every 1000 hours/ 12 months***POWER TAKE OFF FRONT**

Capacity: 0,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE/HYDRAULIC SYSTEM 24/8

Capacity: 38 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DEUTZ-FAHR AGROTRON MKI AGROTRON

4.95 (1995-1997)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 50 hours, change every 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 250 hours

COOLING SYSTEM

Capacity: 15,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.