

DEUTZ-FAHR AGROTRON MKII AGROTRON

160 (1997-2001)



ENGINE Deutz BF6M-1013E
Capacity: 18,5 liter, Filter capacity: 1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 11 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 250 hours, change every 1000 hours/ 12 months

POWER TAKE OFF FRONT
Capacity: 4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-----------------------------|--|--|
| Kroontrak MTH 10W-30 | | |

Check every 50 hours, change every 1000 hours/ 12 months

POWER TAKE OFF FRONT Zuidberg
Capacity: 0,9 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-----------------------------|--|--|
| Abacot MEP Synth 220 | | |

Check every 250 hours

DEUTZ-FAHR AGROTRON MKII AGROTRON 160 (1997-2001)



TRANSAXLE/HYDRAULIC SYSTEM 27/24

Capacity: 105 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 250 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

Check every 50 hours

COOLING SYSTEM

Capacity: 28 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

Check every 10 hours, change every 24 months

AIRCONDITIONING COMPRESSOR

Capacity: 1,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.