

DRONNINGBORG (CASE IH) ALLE MODELLER D 4000S PERKINS 4.236 (1982- 1990)



MOTOR Perkins 4.236
Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
HDX 30		

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
HDX 20W-20		

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
HDX 10W		

Kontroller alle 10 timer, skift alle 250 timer

REDUKTIONSENHEDER FOR
Kapacitet: 4,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 500 timer/ 24 måneder

TRANSAKSEL MANUEL 3/3
Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 500 timer/ 24 måneder

DRONNINGBORG (CASE IH) ALLE MODELLER D 4000S PERKINS 4.236 (1982- 1990)

**HYDRAULISK SYSTEM**

Kapacitet: 32 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Perlus AF 100*Skift alle 1000 timer/ 24 måneder*

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

PRODUKTANBEFALING 2

Perlus AF 68*Skift alle 1000 timer/ 24 måneder***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2**KØLESYSTEM**

Kapacitet: 28 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.