

# DRONNINGBORG (CASE IH) ALL MODELS

## D 4500 PERKINS 6.354.4 (1982-1990)



**ENGINE** Perkins 6.354.4  
Capacity: 13 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**HDX 30**

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**HDX 20W-20**

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**HDX 10W**

*Check every 10 hours, change every 250 hours*

### REDUCTION UNITS FRONT

Capacity: 4,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 500 hours/ 24 months*

### TRANSAXLE MANUAL 3/3

Capacity: 3,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 500 hours/ 24 months*

# DRONNINGBORG (CASE IH) ALL MODELS

## D 4500 PERKINS 6.354.4 (1982-1990)



### HYDRAULIC SYSTEM

Capacity: 32 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
<b>Perlus AF 100</b>		

Change every 1000 hours/ 24 months

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 68</b>	<b>Perlus AF 68</b>	

Change every 1000 hours/ 24 months

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

### COOLING SYSTEM

Capacity: 28 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.