## E-Z-GO GOLF RXV - SHUTTLE 2+2 (PETROL) (2009 AND AFTER)



ENGINE Kawasaki Capacity: 1,25 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak CVT 10W-40	Multifleet SHPD 10W-40	
Check every 10 hours, change every 6 months/ 125 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Check every 10 hours, change every 6 months/ 125 hours		

Normal CLIMATE  Moderate  PRODUCT RECOMMENDATION 1	TRANSAXLE CVT Capacity: 1,5 liter			
PRODUCT RECOMMENDATION 1				
Multifleet SCD 30				

Check every 160 km/ 1 months/ 20 hours, change every 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.