EICHER 3000 3080 AS (1987-1990)



| ENGINE Capacity: 10 liter | | |
|---|-------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| Check every 10 hours, change every 200 kg | hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak MTH 10W-30 | | |
| Check every 10 hours, change every 200 i | hours | |

| DIFFERENTIAL FRONT (4x4) Capacity: 4,5 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 200 hours, change every 1000 hours/12 months

| DIFFERENTIAL REAR (4x4) Capacity: 4,5 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 200 hours, change every 1000 hours/ 12 months

| HUB REDUCTIONS FRONT Capacity: 0,5 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Check every 200 hours, change every | y 600 hours/ 12 months | |

EICHER 3000 3080 AS (1987-1990)



| HUB REDUCTIONS REAR Capacity: 2 liter | | |
|---------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 200 hours, change every 600 hours/ 12 months

| USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 | |
|--|--|
| | |
| PRODUCT RECOMMENDATION 1 | |
| | |
| Kroontrak MTH 10W-30 | |

Check every 6 months/ 200 hours, change every 600 hours/ 12 months

| HYDRAULIC SYSTEM Capacity: 18 liter | | | |
|-------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Perlus H 46 | Perlus AF 46 | | |
| Chack ayon, 50 hours, change ayo | ory 600 hours/12 months | | |

Check every 50 hours, change every 600 hours/ 12 months

| HYDRAULIC BRAKE SYSTEM | | |
|---------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| | | |

Check every 10 hours

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| Check every 200 hours | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.