## **EICHER 3100 3145 E** (1988-1991)



| ENGINE<br>Capacity: 19 liter |                          |               |
|------------------------------|--------------------------|---------------|
| USE                          |                          | CLIMATE       |
| Normal                       |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1     |                          |               |
| Multifleet SCD 30            |                          |               |
| Change every 200 hours       |                          |               |
| USE                          |                          | CLIMATE       |
| Normal                       |                          | Moderate      |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 |               |
| Kroontrak MTH 10W-30         | Multifleet SHPD 10W-40   |               |
| Change every 200 hours       |                          |               |

| <b>DIFFERENTIAL FRONT</b> (4x4)<br>Capacity: 8 liter |                             |          |
|--|-----------------------------|----------|
| USE  |                             | CLIMATE  |
| Normal   |                             | Moderate |
| PRODUCT RECOMMENDATION 1                             | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                                 | Unigear HS GL-3/GL-5 80W-90 |          |

Check every 200 hours, change every 600 hours/ 12 months

| <b>HUB REDUCTIONS FRONT</b> (4x4) Capacity: 1,2 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal  |                             | Moderate |
| PRODUCT RECOMMENDATION 1                              | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                                  | Unigear HS GL-3/GL-5 80W-90 |          |

Check every 200 hours, change every 600 hours/ 12 months

| HUB REDUCTIONS REAR<br>Capacity: 8 liter |                             |          |
|--|-----------------------------|----------|
| USE                                      |                             | CLIMATE  |
| Normal                                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                     | Unigear HS GL-3/GL-5 80W-90 |          |
| Check every 200 hours, change eve        | ery 600 hours/ 12 months    |          |

## EICHER 3100 3145 E (1988-1991)



| TRANSMISSION/HYDRAULIC SYSTEM ZF 20/9 Capacity: 42 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                                 |          |
| Multifleet SCD 20W-20                                    |          |
| Check every 200 hours, change every 600 hours/ 12 mor    | nths     |

HYDRAULIC BRAKE SYSTEM

USE

Normal

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 12 months

| POWER STEERING Capacity: 5 liter               |  |          |
|--|--|----------|
| USE  |  | CLIMATE  |
| Normal   |  | Moderate |
| PRODUCT RECOMMENDATION 1                       |  |          |
| ATF-A  |  |          |
| Check every 200 hours, change every 1000 hours |  |          |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |
| Check every 200 hours    | '                        | '                        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.