## EICHER 4000 4072 (3555) (1977-1983)



ENGINE Perkins A4.248 Capacity: 7,3 liter		
use Normal		climate Tropical
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Check every 10 hours, change every 150 h	nours/ 12 months	
use Normal		climate Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
Check every 10 hours, change every 150 h	nours/ 12 months	
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
Check every 10 hours, change every 150 h	nours/ 12 months	
use Normal		climate Cold
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30		
Check every 10 hours, change every 150 h	nours/ 12 months	
HUB REDUCTIONS REAR Capacity: 2 liter		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
Check every 300 hours, change every 600	hours/ 12 months	
TRANSMISSION/HYDRAULIC SYSTEM	16/4	

Kroontrak CVT 10W-40	Kroontrak MTH 10W-30		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
Capacity: 42 liter			

Check every 150 hours, change every 600 hours/ 12 months

## EICHER 4000 4072 (3555) (1977-1983)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 10 hours, change every 12 months

POWER STEERING Capacity: 3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF-A	
Charle avery 4E0 hours aborre avery 12	

Check every 150 hours, change every 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

COOLING SYSTEM Capacity: 13,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every	/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.