

EICHER 600 (VC/VAC) 680 VAC (2000-2004)



MOTOR EDL 4-5.1

Kapacitet: 11 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 200 timer

DIFFERENTIALE FOR Carraro

Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 200 timer, skift alle 1000 timer/ 12 måneder

GEAR

Kapacitet: 28 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Kontroller alle 200 timer, skift alle 600 timer/ 12 måneder

NAVREDUKTIONER FOR Carraro

Kapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 200 timer, skift alle 1000 timer/ 12 måneder

EICHER 600 (VC/VAC) 680 VAC (2000-2004)



HYDRAULIKSYSTEM SERVOSTYRING

Kapacitet: 24 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

Kontroller alle 200 timer, skift alle 600 timer/ 12 måneder

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 1 måneder, skift alle 24 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.