FARMTRAC F SERIES FARMTRAC FT 7100DT (2012 AND AFTER)



ENGINE Perkins 1104D-44T Capacity: 9,5-10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Change every 300 hours

DIFFERENTIAL FRONT Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 600 hours

HUB REDUCTIONS FRONT Capacity: 1 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 600 hours

TRANSAXLE Capacity: 35 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak CVT 10W-40	

Change every 1000 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 34 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak CVT 10W-40	
Change every 1000 hours/ 12 months	

FARMTRAC F SERIES FARMTRAC FT 7100DT (2012 AND AFTER)



COOLING SYSTEM Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.