

FENDT 200 VARIO COM3 211 S VARIO 334 (2009-2017)



MOTOR Sisu 33CTA
Kapacitet: 10 liter

ANVEND

Normalt, svovlniveau i brændstof < 500 ppm

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

KRAFTOVERFØRING FOR
Kapacitet: 1,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 500 timer, skift alle 2000 timer/ 24 måneder

NAVREDUKTIONER FOR
Kapacitet: 0,8 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

SELVSPÆRRENDE DIFFERENTIALE FOR
Kapacitet: 4,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

FENDT 200 VARIO COM3 211 S VARIO 334 (2009-2017)



TRANSAKSEL Vario
Kapacitet: 30 liter (Servicepåfyldning), Kapacitet: 33 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Kroontrak CVT 10W-40		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
Kroontrak CVT 10W-40		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

HYDRAULISK SYSTEM
Kapacitet: 39 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 1000 timer/ 24 måneder

PNEUMATISK BREMSESYSTEM
Kapacitet: 0,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

KØLESYSTEM
Kapacitet: 12,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUKTANBEFALING

FENDT 200 VARIO COM3 211 S VARIO 334 (2009-2017)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.