

FENDT 300 VARIO COM3B 311 VARIO 324/.. /1001 -> (2012-2014)



MOTOR Deutz TCD 1212 L04 4V
Kapacitet: 11 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 10W-40

Skift alle 50 timer

DIFFERENTIALE FOR
Kapacitet: 7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

KRAFTOVERFØRING FOR
Kapacitet: 1,25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 12 måneder/ 500 timer, skift alle 2000 timer/ 24 måneder

NAVREDUKTIONER FOR
Kapacitet: 0,7 liter (hvert nav)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

FENDT 300 VARIO COM3B 311 VARIO 324/.. /1001 -> (2012-2014)



TRANSAKSEL Vario
Kapacitet: 30 liter (Servicepåfyldning), Kapacitet: 35 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak CVT 10W-40

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak CVT 10W-40

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

HYDRAULISK SYSTEM
Kapacitet: 60 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Multifleet SCD 20W-20

Skift alle 1000 timer/ 24 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak CVT 10W-40

PRODUKTANBEFALING 2
Kroontrak MTH 10W-30

Skift alle 1000 timer/ 24 måneder

PNEUMATISK BREMSESYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

Kontroller alle 50 timer

FENDT 300 VARIO COM3B 311 VARIO 324/.. /1001 -> (2012-2014)



KØLESYSTEM

Kapacitet: 29 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.