

FENDT 500 XYLON XYLON 520 520/./0001 -> (1995-2004)



MOTOR MAN DO824
Kapacitet: 14,5 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 250 timer/ 12 måneder

DIFFERENTIALE FOR (4x4)
Kapacitet: 7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

KRAFTOVERFØRING FOR
Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 500 timer, skift alle 2000 timer/ 24 måneder

FENDT 500 XYLON XYLON 520 520/./0001 -> (1995-2004)



NAVREDUKTIONER BAG

Kapacitet: 7,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 500 timer, skift alle 2000 timer/ 24 måneder

NAVREDUKTIONER FOR (4x4)

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

TRANSAKSEL MANUEL 44/44

Kapacitet: 44 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	

Skift alle 2000 timer/ 24 måneder

HYDRAULISK SYSTEM

Kapacitet: 61 liter

ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Multifleet SCD 20W-20	

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

FENDT 500 XYLON XYLON 520 520/./0001 -> (1995-2004)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 1,1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 500 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER ANDRE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 125 timer

KØLESYSTEM

Kapacitet: 18 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.