

FENDT 800 VARIO COM2 818 VARIO TMS

718/.. /0000 -> 718/.. /2000 (2002-2005)



MOTOR Deutz BF6M-2013C
Kapacitet: 16,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Ved højt sodindhold	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

KRAFTOVERFØRING FOR
Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Kroontrak CVT 10W-40		

Kontroller alle 500 timer, skift alle 2000 timer/ 24 måneder

NAVREDUKTIONER BAG
Kapacitet: 13 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 2000 timer/ 24 måneder

NAVREDUKTIONER FOR
Kapacitet: 2,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 12 måneder/ 500 timer, skift alle 1000 timer/ 24 måneder

FENDT 800 VARIO COM2 818 VARIO TMS

718/.. /0000 -> 718/.. /2000 (2002-2005)



SELVSPÆRRENDE DIFFERENTIALE FOR

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 12 måneder/ 500 timer, skift alle 1000 timer/ 24 måneder

TRANSAKSEL Vario

Kapacitet: 50 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

HYDRAULISK SYSTEM

Kapacitet: 50 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 50 timer, skift alle 1000 timer/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

Kontroller alle 50 timer, skift alle 1000 timer/ 24 måneder

FENDT 800 VARIO COM2 818 VARIO TMS

718/.. /0000 -> 718/.. /2000 (2002-2005)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 12 måneder/ 500 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 20 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.