

FENDT 900 VARIO COM3 FAVORIT 927

VARIO 925/./0101 -> 925/./3500 (2006-2007)



MOTOR Deutz TCD 2013 L06 4V
Kapacitet: 38 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Skift alle 50 timer

DIFFERENTIALE FOR

Kapacitet: 16 liter (Dobbelt bremsesystem), Kapacitet: 34 liter (Enkelt bremsesystem)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Kroontrak CVT 10W-40		

Kontroller alle 12 måneder/ 500 timer, skift alle 1000 timer/ 24 måneder

KRAFTOVERFØRING FOR

Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Kroontrak CVT 10W-40		

Kontroller alle 12 måneder/ 500 timer, skift alle 2000 timer/ 24 måneder

NAVREDUKTIONER BAG

Kapacitet: 17 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

Kontroller alle 12 måneder/ 500 timer, skift alle 2000 timer/ 24 måneder

FENDT 900 VARIO COM3 FAVORIT 927

VARIO 925/./0101 -> 925/./3500 (2006-2007)



NAVREDUKTIONER BAG Stummel

Kapacitet: 16 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

NAVREDUKTIONER FOR

Kapacitet: 4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

Kontroller alle 12 måneder/ 500 timer, skift alle 1000 timer/ 24 måneder

TRANSAXSEL Vario

Kapacitet: 67 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Kroontrak CVT 10W-40		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1		
Kroontrak CVT 10W-40		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

FENDT 900 VARIO COM3 FAVORIT 927

VARIO 925/.. /0101 -> 925/.. /3500 (2006-2007)



HYDRAULISK SYSTEM

Kapacitet: 109 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Multifleet SCD 20W-20		

Kontroller alle 12 måneder/ 500 timer, skift alle 1000 timer/ 24 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	

Kontroller alle 12 måneder/ 500 timer, skift alle 1000 timer/ 24 måneder

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0,25 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 12 måneder/ 500 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 30 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.