

FENDT FARMER 300 C FARMER 309 C

119/.. /5001 -> (1998-2001)

**ENGINE**

Capacity: 11 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3

AgriDiesel MSP 15W-40*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 10 hours, change every 500 hours/ 12 months***DIFFERENTIAL FRONT**

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 500 hours, change every 1000 hours/ 12 months***HUB REDUCTIONS FRONT**

Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 500 hours, change every 1000 hours/ 12 months*

FENDT FARMER 300 C FARMER 309 C

119/.. /5001 -> (1998-2001)



HUB REDUCTIONS REAR

Capacity: 5,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 12 months/ 500 hours, change every 2000 hours/ 24 months

POWER TAKE OFF FRONT

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 12 months/ 500 hours, change every 2000 hours/ 24 months

TRANSAXLE MANUAL 21/21

Capacity: 37,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 2000 hours/ 24 months

HYDRAULIC SYSTEM

Capacity: 41 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 1000 hours/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	

Change every 1000 hours/ 24 months

FENDT FARMER 300 C FARMER 309 C

119/.. /5001 -> (1998-2001)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 500 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

COOLING SYSTEM

Capacity: 13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.