PRODUCT RECOMMENDATION

# FENDT FARMER 300 FARMER 309 TURBO 309/../00001 -> (1993-2001)

**ENGINE** TD 226 4B
Capacity: 11 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 40** | | |

*Change every 250 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 30** | | |

*Change every 250 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Kroontrak MTH 10W-30** | **Multifleet SHPD 10W-40** | **Multifleet SHPD 15W-40** |

*Change every 250 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 10W** | | |

*Change every 250 hours/ 12 months*

**DIFFERENTIAL FRONT** (4x4)
Capacity: 7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 500 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT** (4x4)
Capacity: 0,75 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 500 hours, change every 1000 hours/ 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# FENDT FARMER 300 FARMER 309 TURBO 309/../00001 -> (1993-2001)

## HUB REDUCTIONS REAR
Capacity: 5,7 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 500 hours, change every 1000 hours/ 12 months*

## POWER TAKE OFF FRONT
Capacity: 1 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 500 hours*

## TRANSAXLE MANUAL 21/21
Capacity: 34,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 500 hours, change every 1000 hours/ 12 months*

## HYDRAULIC SYSTEM
Capacity: 12 liter

| USE | CLIMATE |
|---|---|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 30** | | |

*Check every 500 hours, change every 1000 hours/ 12 months*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Kroontrak MTH 10W-30** | **Multifleet SCD 20W-20** | |

*Check every 500 hours, change every 1000 hours/ 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# FENDT FARMER 300 FARMER 309 TURBO 309/../00001 -> (1993-2001)

## FLUID CLUTCH
Capacity: 7,1 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 10W** | | |

*Change every 5000 hours*

## HYDRAULIC BRAKE SYSTEM
Capacity: 0,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Check every 500 hours, change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES 3-POINT HITCH

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 250 hours*

## GREASE POINTS/NIPPLES OTHERS

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Check every 125 hours*

## COOLING SYSTEM
Capacity: 13 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** | |

*Check every 500 hours, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367