PRODUCT RECOMMENDATION

FENDT FAVORIT 600 FAVORIT 615 LSA 385/../0001 -> 385/21/2001 (1985-1988)

ENGINE TD 226 B6
Capacity: 17 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

Change every 250 hours/ 12 months

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SHPD 15W-40	**Multifleet SCD 30**	

Change every 250 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Kroontrak MTH 10W-30	**Multifleet SCD 10W**	

Change every 250 hours/ 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 250 hours/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 250 hours, change every 1000 hours/ 24 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 250 hours, change every 1000 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FENDT FAVORIT 600 FAVORIT 615 LSA 385/../0001 -> 385/21/2001 (1985-1988)

HUB REDUCTIONS REAR
Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 250 hours, change every 1000 hours/ 24 months

POWER TAKE OFF FRONT
Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 250 hours/ 6 months

TRANSMISSION MANUAL ZF 20/9
Capacity: 55 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 250 hours, change every 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	**Multifleet SCD 20W-20**	

Check every 250 hours, change every 12 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FENDT FAVORIT 600 FAVORIT 615 LSA 385/../0001 -> 385/21/2001 (1985-1988)

POWER STEERING
Capacity: 8 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 250 hours, change every 1000 hours/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	**Multifleet SCD 20W-20**	

Check every 250 hours, change every 1000 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 125 hours

COOLING SYSTEM
Capacity: 23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 250 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367