

# FENDT 700 VARIO COM1/2 711 VARIO (2003-2006)



**ENGINE** Deutz BF6M-2013C  
Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
When experiencing high soot levels	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Change every 50 hours*

**DIFFERENTIAL FRONT LIMITED SLIP**  
Capacity: 6-8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 50 hours*

# FENDT 700 VARIO COM1/2 711 VARIO (2003-2006)



## HUB REDUCTIONS FRONT

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

Change every 50 hours

## HUB REDUCTIONS REAR

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

Check every 12 months/ 500 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

Change every 500 hours

## POWER TAKE OFF FRONT

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Kroontrak CVT 10W-40</b>		

Check every 12 months/ 500 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Kroontrak CVT 10W-40</b>		

Change every 500 hours

# FENDT 700 VARIO COM1/2 711 VARIO (2003-2006)



## TRANSAXLE Vario

Capacity: 50 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Kroontrak CVT 10W-40</b>		

*Check every 10 hours, change every 2000 hours/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>Kroontrak CVT 10W-40</b>		

*Check every 10 hours, change every 2000 hours/ 24 months*

## HYDRAULIC SYSTEM

Capacity: 50 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		

*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak CVT 10W-40</b>	<b>Kroontrak MTH 10W-30</b>	

*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

## HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

*Check every 12 months/ 500 hours, change every 2000 hours/ 24 months*

## PNEUMATIC BRAKE SYSTEM

Capacity: 0,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**FENDT 700 VARIO COM1/2 711 VARIO (2003-2006)****GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

**COOLING SYSTEM**

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*