

FENDT TOOLCARRIER 370 GT 148/./00001 - > (1998-2004)



ENGINE Deutz F4L-913FH
Capacity: 10,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel MSP 15W-40*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
First change only	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Change every 50 hours*

USE	CLIMATE
First change only	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 50 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel MSP 15W-40*Change every 50 hours*

FENDT TOOLCARRIER 370 GT 148/./00001 - > (1998-2004)



USE		CLIMATE
First change only		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Change every 50 hours</i>		

DIFFERENTIAL FRONT Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 50 hours, change every 2000 hours/ 24 months</i>		

HUB REDUCTIONS FRONT Capacity: 0,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 50 hours, change every 2000 hours/ 24 months</i>		

POWER TAKE OFF FRONT Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 50 hours, change every 2000 hours/ 24 months</i>		

REDUCTION UNITS REAR Capacity: 3,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 50 hours, change every 2000 hours/ 24 months</i>		



FENDT TOOLCARRIER 370 GT 148/./00001 - > (1998-2004)



TRANSAXLE MANUAL

Capacity: 27,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 50 hours, change every 2000 hours/ 24 months

HYDRAULIC SYSTEM

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SCD 20W-20	

Check every 250 hours, change every 1000 hours/ 24 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 50 hours, change every 24 months

PNEUMATIC BRAKE SYSTEM

Capacity: 0,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 125 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.