FERRARI COBRAM COBRAM 50 AR (2001 AND AFTER)



| ENGINE Lombardini LDW2004 Capacity: 5,3 liter | | |
|------------------------------------------------------|-------|---------------|
| USE | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 40 | | |
| Check every 10 hours, change every 125 l | hours | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 20W-20 | | |
| Check every 10 hours, change every 125 l | hours | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| Check every 10 hours, change every 125 l | hours | |
| | | |

| DIFFERENTIAL FRONT Capacity: 6,5 liter | | | |
|-----------------------------------------------|--------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Agrifluid HT | | | |
| Check every 100 hours, change eve | rv 600 hours | | |

| TRANSAXLE MANUAL 12/12 Capacity: 14,5 liter | | |
|------------------------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 100 hours, change every 600 hours | | |

FERRARI COBRAM COBRAM 50 AR (2001 AND AFTER)



| Charles and EO harries | | |
|--------------------------|--------------------------|--------------------------|
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2 | Q5 MP Calcep Grease EP 2 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |
| GREASE POINTS/NIPPLES | | |

Check every 50 hours

| COOLING SYSTEM Capacity: 8,5 liter | | | |
|------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Charle avery 10 hours shangs aver | 1000 hours | | |

Check every 10 hours, change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.