

# FERRARI SYSTEM SERIES SYSTEM 70 (RS/MT) (1995 AND AFTER)



**ENGINE** VM 394HPT  
Capacity: 5,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agridiesel CRD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Check every 10 hours, change every 125 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agridiesel CRD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 50 hours*

**DIFFERENTIAL FRONT**  
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		

*Check every 100 hours, change every 600 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		

*Check every 100 hours, change every 600 hours*

**TRANSAXLE MANUAL**  
Capacity: 19,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		

*Check every 50 hours, change every 600 hours*

# FERRARI SYSTEM SERIES SYSTEM 70 (RS/MT) (1995 AND AFTER)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Q7 MP Calcep Grease WR 2</b>	<b>Caliplex HD Grease EP 2</b>	<b>Q5 MP Calcep Grease EP 2</b>

*Check every 50 hours*

## COOLING SYSTEM

Capacity: 3,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*