

# FIAT-TRATTORI 80 1380, 1380 DT (1980-1984)



## MOTOR 8065

Kapacitet: 15,2 liter, Filterkapacitet: 1,9 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Multifleet SCD 30**

*Skift alle 200 timer*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Multifleet SCD 20W-20**

*Skift alle 200 timer*

## DIFFERENTIALE FOR (4x4)

Kapacitet: 10,8 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

*Kontroller alle 400 timer, skift alle 1600 timer*

## GEAR MANUEL 24/8

Kapacitet: 18,3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

*Kontroller alle 400 timer, skift alle 1600 timer*

## NAVREDUKTIONER FOR (4x4)

Kapacitet: 2,1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

*Kontroller alle 400 timer, skift alle 1600 timer*

# FIAT-TRATTORI 80 1380, 1380 DT (1980-1984)



## HYDRAULISK SYSTEM/BAGAKSEL

Kapacitet: 44,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

PRODUKTANBEFALING 2

**Agrifluid HT**

*Kontroller alle 400 timer, skift alle 1600 timer*

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Multifleet SCD 10W**

## SERVOSTYRING

Kapacitet: 2,4 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

*Skift alle 800 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

*Skift alle 800 timer*

## SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Q7 MP Calcep Grease WR 2**

PRODUKTANBEFALING 2

**Caliplex HD Grease EP 2**

*Kontroller alle 50 timer*

# FIAT-TRATTORI 80 1380, 1380 DT (1980-1984)



## SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Q7 MP Calcep Grease WR 2**

PRODUKTANBEFALING 2

**Caliplex HD Grease EP 2**

*Kontroller alle 400 timer*

## KØLESYSTEM

Kapacitet: 17 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

*Skift alle 1600 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*