

FIAT-TRATTORI 80 880, 880 DT (1975-1981)



MOTOR Mercedes-Benz OM C03/75
Kapacitet: 13,4 liter, Filterkapacitet: 0,6 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Skift alle 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

Skift alle 200 timer

DIFFERENTIALE FOR (4x4)
Kapacitet: 6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Kontroller alle 400 timer, skift alle 1600 timer

GEAR MANUEL 8/2
Kapacitet: 11,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Kontroller alle 400 timer, skift alle 1600 timer

NAVREDUKTIONER FOR (4x4)
Kapacitet: 1,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Kontroller alle 400 timer, skift alle 1600 timer

FIAT-TRATTORI 80 880, 880 DT (1975-1981)



HYDRAULISK SYSTEM/BAGAKSEL

Kapacitet: 44,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Kontroller alle 400 timer, skift alle 1600 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

SERVOSTYRING

Kapacitet: 1,7 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

Skift alle 800 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

Skift alle 800 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2

Caliplex HD Grease EP 2

Kontroller alle 50 timer

FIAT-TRATTORI 80 880, 880 DT (1975-1981)



SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q7 MP Calcep Grease WR 2

PRODUKTANBEFALING 2

Caliplex HD Grease EP 2

Kontroller alle 400 timer

KØLESYSTEM

Kapacitet: 18 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 1600 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.