PRODUCT RECOMMENDATION

FIAT-TRATTORI G SERIES G 170 (1993-2002)

ENGINE
Capacity: 21 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		

Check every 10 hours, change every 300 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	**Multifleet SHPD 10W-40**	

Check every 10 hours, change every 300 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 12,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 300 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 300 hours, change every 1200 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 36/18
Capacity: 140 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 10 hours, change every 900 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FIAT-TRATTORI G SERIES G 170 (1993-2002)

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Check every 50 hours		

COOLING SYSTEM
Capacity: 26,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		
Check every 10 hours, change every 2400 hours/ 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367