

**FORD 10 3610 (1981-1983)****ENGINE**

Capacity: 6,6 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Check every 10 hours, change every 300 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Check every 10 hours, change every 300 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30***Check every 10 hours, change every 300 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 10 hours, change every 300 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Unigear HS GL-3/GL-5 80W-90***Check every 50 hours, change every 1200 hours***DIFFERENTIAL REAR/HYDRAULIC SYSTEM**

Capacity: 23,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Agrifluid HT***Check every 50 hours, change every 1200 hours*

**FORD 10 3610 (1981-1983)****HUB REDUCTIONS FRONT (4x4)**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	<b>Gearlube LS 80W-90</b>

*Check every 50 hours, change every 1200 hours***TRANSMISSION MANUAL 8/2**

Capacity: 9,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>	

*Check every 300 hours, change every 1200 hours***POWER STEERING**

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>ATF Dexron II-D</b>	<b>ATF-A</b>	

*Check every 300 hours, change every 1200 hours/ 12 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Labora Grease</b>	<b>MoS2 Grease EP 2</b>	

*Check every 50 hours***GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Labora Grease</b>	<b>MoS2 Grease EP 2</b>	

*Check every 50 hours, change every 600 hours*

**FORD 10 3610 (1981-1983)****COOLING SYSTEM**

Capacity: 10,4 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 11****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 10 hours, change every 2400 hours/ 24 months***BELT PULLEY**

Capacity: 0,57 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Agrifluid HT***Check every 50 hours, change every 1200 hours***STEERING BOX**

Capacity: 0,64 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Unigear HS GL-3/GL-5 80W-90***Check every 600 hours, change every 1200 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*