FORD 20 1120 (1988-1996)

Check every 10 hours, change every 100 hours



ENGINE Capacity: 3,3 liter, Filter capacity: 0,3 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	Multifleet SCD 30	
Check every 10 hours, change every 100	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Check every 10 hours, change every 100	hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

DIFFERENTIAL FRONT (4x4) Capacity: 1,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90
Check every 50 hours, change eve	ry 300 hours	I

TRANSAXLE/HYDRAULIC SYSTE Capacity: 16 liter	M 9/3	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Agrifluid HT	
Check every 50 hours, change every	y 300 hours	

KROON-OIL B.V. Postbus 149 7600 AC Almelo

FORD 20 1120 (1988-1996)



TRANSMISSION HYDROSTATIC Capacity: 16 liter	2/2		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
ATF Dexron II-D	ATF-A		
		·	

Check every 50 hours, change every 300 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	MoS2 Grease EP 2	
Check every 50 hours		

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	MoS2 Grease EP 2	
Check every 600 hours		

COOLING SYSTEM Capacity: 3,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours	'	'	

STEERING BOX		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Agrifluid HT

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.