

**FORD 80 8060 FIAT 8061 SI (1978-1988)**

**ENGINE** Fiat 8061 SI  
Capacity: 12,5 liter, Filter capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Check every 10 hours, change every 100 hours/ 12 months*

**TRANSAXLE MANUAL** 4/1  
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 50 hours, change every 500 hours/ 12 months*

**HYDRAULIC SYSTEM**  
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF-A**

PRODUCT RECOMMENDATION 2

**Perlus H 46**

PRODUCT RECOMMENDATION 3

**Perlus AF 46***Check every 10 hours, change every 500 hours/ 12 months*

**HYDRAULIC BRAKE/CLUTCH SYSTEM**  
Capacity: 0,33 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 50 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**MoS2 Grease EP 2**

PRODUCT RECOMMENDATION 3

**Q5 MP Calcep Grease EP 2***Check every 10 hours*

**FORD 80 8060 FIAT 8061 SI (1978-1988)****GREASE POINTS/NIPPLES AUGER DRIVE GEARBOX**

We are unable to give a standard recommendation for this component. Please contact our service department.

**GREASE POINTS/NIPPLES ROTOR-THRESHER GEARBOX**

We are unable to give a standard recommendation for this component. Please contact our service department.

**COOLING SYSTEM**

Capacity: 36 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*