

FORD FW FW-40 (1979 AND AFTER)

ENGINE Cummins V903
Capacity: 35,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 100 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20*Change every 100 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 100 hours*

DIFFERENTIAL FRONT (4x4)
Capacity: 26,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear HS GL-3/GL-5 80W-90*Check every 100 hours, change every 500 hours*

HUB REDUCTIONS FRONT (4x4)
Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear HS GL-3/GL-5 80W-90*Check every 100 hours, change every 500 hours*

FORD FW FW-40 (1979 AND AFTER)**TRANSMISSION MANUAL/TRANSFERBOX 10/2**

Capacity: 56,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT***Check every 100 hours, change every 500 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 94,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D****PRODUCT RECOMMENDATION 2****ATF-A***Check every 10 hours, change every 1000 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid DOT 3***Check every 100 hours***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid DOT 3***Check every 100 hours***GREASE POINTS/NIPPLES CLUTCH RELEASE BEARING****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**MoS2 Grease EP 2***Check every 100 hours*

FORD FW FW-40 (1979 AND AFTER)**GREASE POINTS/NIPPLES OTHERS**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease*Check every 50 hours***COOLING SYSTEM**

Capacity: 64 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 10 hours, change every 2400 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.