

FORD TW TW-10 (1979-1983)**ENGINE**

Capacity: 19 liter, Filter capacity: 2 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 10 hours, change every 300 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20*Check every 10 hours, change every 300 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30*Check every 10 hours, change every 300 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 10 hours, change every 300 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear HS GL-3/GL-5 80W-90*Check every 50 hours, change every 1200 hours***HUB REDUCTIONS FRONT (4x4)**

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear HS GL-3/GL-5 80W-90*Check every 50 hours, change every 1200 hours*

FORD TW TW-10 (1979-1983)**POWER TAKE OFF**

Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 50 hours, change every 1200 hours***TRANSAXLE/HYDRAULIC SYSTEM 8/2**

Capacity: 60,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 50 hours, change every 1200 hours***POWER STEERING**

Capacity: 3,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

PRODUCT RECOMMENDATION 2

ATF-A*Check every 300 hours, change every 1200 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

MoS2 Grease EP 2*Check every 50 hours***GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

MoS2 Grease EP 2*Check every 50 hours, change every 600 hours*

FORD TW TW-10 (1979-1983)**COOLING SYSTEM**

Capacity: 20 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 11****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 10 hours, change every 2400 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.