HARDI SPRAYERS ALPHA 2500 DEUTZ BF6M 1012 (1997-2006)



Agridiesel CRD+ 15W-40		
PRODUCT RECOMMENDATION 1		
Initial service		Moderate
USE		CLIMATE
Check every 10 hours, change every 500 h	nours	
Agridiesel CRD+ 15W-40		
PRODUCT RECOMMENDATION 1		
Normal		Moderate
USE		CLIMATE
ENGINE Deutz BF6M-1012 Capacity: 15 liter, Filter capacity: 1,5 liter		

Change every 50 hours

HYDROSTATIC DRIVE Capacity: 60 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Charle avery 10 hours shange avery 1000	hours	

Check every 10 hours, change every 1000 hours

use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 10 hours, change every 500 h	nours	

 GREASE POINTS/NIPPLES CHASSIS AND BOOM

 USE
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 Modes

 MoS2 Grease EP 2
 Image: Climate

Change every 50 hours

HARDI SPRAYERS ALPHA 2500 DEUTZ BF6M 1012 (1997-2006)



GREASE POINTS/NIPPLES DIAPHRAGM PUMP		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

GREASE POINTS/NIPPLES OIL LUBRICATED		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

COOLING SYSTEM Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 100 hours, change eve	ry 2000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.