

# HARDI SPRØJTER ALPHA 2500 DEUTZ BF6M 1012C (1997-2006)



## MOTOR Deutz BF6M-1012C

Kapacitet: 15 liter, Filterkapacitet: 1,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

### PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

*Kontroller alle 10 timer, skift alle 500 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

### PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

*Skift alle 50 timer*

## HYDROSTATISK DREV

Kapacitet: 60 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

### PRODUKTANBEFALING 1

**Perlus Biosynth 46**

### PRODUKTANBEFALING 2

**Perlus H 46**

*Kontroller alle 10 timer, skift alle 1000 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

### PRODUKTANBEFALING 1

**Perlus Biosynth 46**

### PRODUKTANBEFALING 2

**Perlus H 46**

*Kontroller alle 10 timer, skift alle 500 timer*

## SMØREPUNKTER/NIPLER CHASSIS OG BOM

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

### PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

*Skift alle 50 timer*

# HARDI SPRØJTER ALPHA 2500 DEUTZ BF6M 1012C (1997-2006)



## SMØREPUNKTER/NIPLER MELLEMPUMPE

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

*Skift alle 50 timer*

## SMØREPUNKTER/NIPLER SMURT MED OLIE

|                                                    |                                                           |                  |
|----------------------------------------------------|-----------------------------------------------------------|------------------|
| ANVEND<br>Normal                                   |                                                           | KLIMA<br>Moderat |
| PRODUKTANBEFALING 1<br><b>Gearlube GL-5 80W-90</b> | PRODUKTANBEFALING 2<br><b>Unigear HS GL-3/GL-5 80W-90</b> |                  |

*Skift alle 50 timer*

## KØLESYSTEM Kapacitet: 14 liter

|                                                      |                                           |                  |
|------------------------------------------------------|-------------------------------------------|------------------|
| ANVEND<br>Normal                                     |                                           | KLIMA<br>Moderat |
| PRODUKTANBEFALING 1<br><b>Coolant -38 Organic NF</b> | PRODUKTANBEFALING 2<br><b>Coolant -26</b> |                  |

*Kontroller alle 100 timer, skift alle 2000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*