## **HARDI SPRAYERS SPM-OLH (53 KW)** (1999-2006)



ENGINE Deutz BF4L-913	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SHPD 15W-40	

Check every 10 hours, change every 250 hours/ 12 months

<b>DIFFERENTIAL REAR</b> Hurth Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
06	

Check every 10 hours, change every 500 hours

USE CLIMATE Normal Moderate  PRODUCT RECOMMENDATION 1  ATF-F (Ford)	GEARBOX Capacity: 1,8 liter	
PRODUCT RECOMMENDATION 1	USE	CLIMATE
	Normal	Moderate
ATF-F (Ford)	PRODUCT RECOMMENDATION 1	
(. 4.4)	ATF-F (Ford)	

Check every 10 hours, change every 500 hours

HUB REDUCTIONS Capacity: 1,3 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM Capacity: 43 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 10 hours, change every 100	00 hours/ 12 months	

## **HARDI SPRAYERS SPM-OLH (53 KW)** (1999-2006)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 10 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES BALL BEARINGS  USE  CLIMATE		
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

GREASE POINTS/NIPPLES OIL LUBRICATED		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Change every 50 hours	·	

GREASE POINTS/NIPPLES PIVOT PINS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 50 hours		

GREASE POINTS/NIPPLES SLIDE BEARINGS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 50 hours		

## HARDI SPRAYERS SPM-OLH (53 KW) (1999-2006)



REDUCTION GEARBOX Capacity: 1,5-2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90 Unigear HS GL-3/GL-5 80W-90		
Check every 10 hours, change ever	v 500 hours	

Check every 10 hours, change every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.