

**HOLDER A SERIES A 60 (1979-1990)****ENGINE 6001-3**

Capacity: 6 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**HDX 30***Change every 150 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**HDX 20W-20***Change every 150 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**HDX 10W***Change every 150 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 10,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**SP Gear 5015**

PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W***Change every 1500 hours/ 12 months***HUB REDUCTIONS FRONT**

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**SP Gear 5015**

PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W***Check every 300 hours, change every 1500 hours*

**HOLDER A SERIES A 60 (1979-1990)****HUB REDUCTIONS REAR**

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

*Check every 300 hours, change every 1500 hours***TRANSAXLE MANUAL 12/4**

Capacity: 6,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

*Change every 1500 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>HDX 20W-20</b>		

*Check every 150 hours, change every 12 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 150 hours***GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 150 hours*

**HOLDER A SERIES A 60 (1979-1990)****GREASE POINTS/NIPPLES OTHERS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 150 hours*

**COOLING SYSTEM**

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*