

# HOLDER A SERIES A 860 GENERATION

## 2000 (1994 AND AFTER)



**ENGINE** KHD BF4L-1011T  
Capacity: 11,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 40</b>	<b>Multifleet SCD 30</b>	

*Change every 450 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Multifleet SHPD 10W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 450 hours/ 12 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		

*Change every 450 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 450 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

*Check every 150 hours, change every 1350 hours/ 12 months*

**HUB REDUCTIONS FRONT**  
Capacity: 1,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

*Check every 150 hours, change every 900 hours/ 12 months*

# HOLDER A SERIES A 860 GENERATION

## 2000 (1994 AND AFTER)



### TRANSAXLE MANUAL 12/4

Capacity: 11,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

*Check every 150 hours, change every 1350 hours/ 12 months*

### TRANSAXLE MANUAL WITH CREEPER GROUP 12/4

Capacity: 12,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

*Check every 150 hours, change every 1350 hours/ 12 months*

### HYDRAULIC SYSTEM

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

*Check every 150 hours, change every 2700 hours/ 12 months*

### HYDRAULIC BRAKE SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 150 hours, change every 12 months*

### HYDRAULIC CLUTCH SYSTEM

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 150 hours, change every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is*

PRODUCT RECOMMENDATION

# **HOLDER A SERIES A 860 GENERATION 2000 (1994 AND AFTER)**



*advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*