HOLDER B B 19 (1984-1990)



ENGINE Hatz E950 Capacity: 3 liter		
USE	c	CLIMATE
Normal	T	ropical ropical
PRODUCT RECOMMENDATION 1		
HDX 30		
Change every 150 hours		
USE	С	CLIMATE
Normal	N	Moderate
PRODUCT RECOMMENDATION 1		
HDX 20W-20		
Change every 150 hours		
USE	c	CLIMATE
Normal	A	Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 150 hours		

HUB REDUCTIONS REAR Capacity: 0,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Check every 300 hours, change ev	rery 600 hours	1

TRANSAXLE MANUAL 6/3 Capacity: 3,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Check every 300 hours, change ev	ery 1000 hours	,

HOLDER B B 19 (1984-1990)



HYDRAULIC SYSTEM Capacity: 1,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HDX 20W-20		

Check every 150 hours, change every 12 months

GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 1000 hours	'	

Check every 1000 hours

GREASE POINTS/NIPPLES OTHERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 150 hours	I	

STEERING BOX Capacity: 0,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Check every 300 hours	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.