HOLDER C-TRAC C-TRAC C 9.72 (2002 AND AFTER)



ENGINE Deutz BF4M-1011 Capacity: 12,5-14 liter, Filter capacity: 0,5 l	iter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
Charle avery EQ hours ahanga avery EQQ h	aura/12 mantha	

Check every 50 hours, change every 500 hours/ 12 months

TRANSMISSION FRONT Capacity: 10,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 1500 hours/ 12 month	IS In the second s	·
USE		CLIMATE
First change only		Moderate

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

Change every 150 hours

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 1

TRANSMISSION REAR Capacity: 17,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 1500 hours/ 12 month	IS	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

 Agrifluid HT-Plus
 Kroontrak MTH 10W-30
 Agrifluid HT

Change every 150 hours

PRODUCT RECOMMENDATION 3

Agrifluid HT

HOLDER C-TRAC C-TRAC C 9.72 (2002 AND AFTER)



HYDRAULIC SYSTEM Capacity: 45-50 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Check every 125 hours, change every 150	00 hours	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
C/		

Change every 500 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 125 hours, change every 12 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 125 hours, change every 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours	,	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.