PRODUCT RECOMMENDATION HÜRLIMANN XA XA 607, DT (1997-2001)



| ENGINE Perkins H-1000.4 W4 Capacity: 11 liter | | | |
|--|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | | | |
| Multifleet SCD 30 | | | |
| Change every 150 hours | | | |
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 | Multifleet SCD 40 | |
| 01 (50.1 | | · | |

Change every 150 hours

| DIFFERENTIAL FRONT (4x4) Capacity: 6 liter | | |
|--|-----|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| 04 | 0.1 | |

Check every 150 hours, change every 1200 hours

| HUB REDUCTIONS FRONT (4x4) Capacity: 1,5 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT | |
| | |

Check every 150 hours, change every 1200 hours

| POWER TAKE OFF FRONT Capacity: 2,5 liter | | |
|---|---------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 150 hours, change every 120 | 0 hours | |



| TRANSAXLE/HYDRAULIC SYSTEM 20/10 Capacity: 41 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| | | |

Check every 150 hours, change every 1200 hours

| HYDRAULIC BRAKE/CLUTCH SYSTEM | | |
|-------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |
| Change aven 21 months | | |

Change every 24 months

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 50 hours

| COOLING SYSTEM Capacity: 11 liter | | |
|--------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Change every 24 months | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.