

HÜRLIMANN XL COM3 XL160 DCR ->20001

(2010 AND AFTER)



ENGINE Deutz TCD 2012 L06 2V DCR
Capacity: 13 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 500 hours

USE	CLIMATE
Biodiesel B100	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT
Capacity: 5,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 0,8 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS REAR
Capacity: 9 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 250 hours, change every 1000 hours/ 12 months

HÜRLIMANN XL COM3 XL160 DCR ->20001

(2010 AND AFTER)



POWER TAKE OFF FRONT

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 250 hours, change every 500 hours

TRANSMISSION MANUAL

Capacity: 78-80 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 50 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.