

# HÜRLIMANN XL COM3 XL175 DCR ->20001

## (2010 AND AFTER)



**ENGINE** Deutz TCD 2012 L06 4V DCR  
Capacity: 16 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Biodiesel B100	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Check every 10 hours, change every 250 hours*

### DIFFERENTIAL FRONT

Capacity: 5,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 250 hours, change every 1000 hours/ 12 months*

### HUB REDUCTIONS FRONT

Capacity: 0,8 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 250 hours, change every 1000 hours/ 12 months*

### HUB REDUCTIONS REAR

Capacity: 9 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 250 hours, change every 1000 hours/ 12 months*

# HÜRLIMANN XL COM3 XL175 DCR ->20001

## (2010 AND AFTER)



### POWER TAKE OFF FRONT

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

Check every 250 hours, change every 500 hours

### TRANSMISSION MANUAL

Capacity: 78-80 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

Check every 50 hours, change every 1000 hours/ 12 months

### HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

Check every 50 hours

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Change every 50 hours

### COOLING SYSTEM

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 12 EVO</b>		

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.