

# HÜRLIMANN XL XL 150.7 (2006-2009)



**ENGINE** Deutz BF6M-1013EC  
Capacity: 18,5 liter, Filter capacity: 1 liter

<b>USE</b> Normal	<b>CLIMATE</b> Moderate
----------------------	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agridiesel MSP 15W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agridiesel CRD+ 15W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Multifleet SHPD 15W-40</b>
---	--	--

*Check every 10 hours, change every 500 hours/ 12 months*

<b>USE</b> Initial service	<b>CLIMATE</b> Moderate
-------------------------------	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agridiesel MSP 15W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agridiesel CRD+ 15W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Multifleet SHPD 15W-40</b>
---	--	--

*Change every 50 hours*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 5,8 liter

<b>USE</b> Normal	<b>CLIMATE</b> Moderate
----------------------	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Gearlube LS 80W-90</b>		
--	--	--

*Check every 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT (4x4)**  
Capacity: 0,8 liter

<b>USE</b> Normal	<b>CLIMATE</b> Moderate
----------------------	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Gearlube LS 80W-90</b>		
--	--	--

*Check every 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS REAR**  
Capacity: 9 liter

<b>USE</b> Normal	<b>CLIMATE</b> Moderate
----------------------	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Gearlube LS 80W-90</b>		
--	--	--

*Check every 250 hours, change every 1000 hours/ 12 months*



# HÜRLIMANN XL XL 150.7 (2006-2009)



## POWER TAKE OFF FRONT

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 50 hours, change every 1000 hours/ 12 months*

## TRANSAXLE/HYDRAULIC SYSTEM 40/40

Capacity: 78-80 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

*Check every 250 hours, change every 1000 hours/ 12 months*

## HYDRAULIC BRAKE SYSTEM

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**LHM +**

*Check every 250 hours, change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

*Check every 50 hours*

## COOLING SYSTEM

Capacity: 28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF**

*Check every 10 hours, change every 24 months*

PRODUCT RECOMMENDATION

# HÜRLIMANN XL XL 150.7 (2006-2009)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*