ISEKI SF SFH220T (2008 AND AFTER)



ENGINE E3112 Capacity: 2,6 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Check every 10 hours, change every	300 hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	Multifleet SCD 30	
Check every 10 hours, change every	300 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Check every 10 hours, change every 3	300 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 3	300 hours	
		CLIMATE
		Tropical
First change only		
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40		
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40		
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE		Tropical
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE First change only		Tropical
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Tropical
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SCD 30	Tropical
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40 Change every 50 hours		CLIMATE Mediterranean
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40 Change every 50 hours USE		CLIMATE Mediterranean CLIMATE
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40 Change every 50 hours USE First change only	Multifleet SCD 30	CLIMATE Mediterranean
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 40 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30		CLIMATE Mediterranean CLIMATE

ISEKI SF SFH220T (2008 AND AFTER)



USE	CLIMATE
First change only	Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	

DIFFERENTIAL REAR Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 10 hours, change every 300 hours

USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W	
Change every 50 hours			

Change every 50 hours

GEARBOX MOWERDECKS SMM Capacity: 0,4 liter	54F	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Change every 200 hours		
USE		CLIMATE

First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Change every 50 hours		

ISEKI SF SFH220T (2008 AND AFTER)



TRANSAXLE HYDROSTATIC Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 200	hours	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Change every 50 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours		

COOLING SYSTEM Capacity: 4,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check eveny 10 hours change even	v 12 months	

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.