ISEKI SGR SGR 22HU (1998 AND AFTER)



ENGINE E3112-G01 Capacity: 2,5 liter			
use Normal		climate Moderate	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40		

Check every 10 hours, change every 100 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	

Change every 50 hours

GEARBOX MOWERDECKS SCM48/SCM54 Capacity: 0,4 liter			
use Normal		сымате Moderate	
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W	

Check every 100 hours, change every 200 hours

TRANSAXLE HYDROSTATIC Capacity: 6,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Kroontrak MTH 10W-30	Agrifluid HT		
0/ / / / /	2021		

Check every 10 hours, change every 300 hours

TRANSFERBOX MOWERDECKS Capacity: 0,11 liter	SCM48/SCM54	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
Check every 100 hours, change ev	ery 200 hours	'

ISEKI SGR SGR 22HU (1998 AND AFTER)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours	-	'

COOLING SYSTEM Capacity: 4,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Chack avery 10 hours, change aver	12 months		

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.