ISEKI TK TK 527 F (1998 AND AFTER)



use Normal		сымате Mediterranean
Multifleet SHPD 15W-40	Multifleet SCD 30	
Check every 10 hours, change every	/ 150 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Check every 10 hours, change every	/ 150 hours	
USE		CLIMATE
First change only		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	Multifleet SCD 30	
Change every 50 hours		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
		

DIFFERENTIAL FRONT (4x4) Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
01 1 101 1 0001	<u>'</u>

Check every 10 hours, change every 200 hours

TRANSAXLE/HYDRAULIC SYSTEM 16/16 Capacity: 23 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Check every 10 hours, change every 200 hours		

ISEKI TK TK 527 F (1998 AND AFTER)



POWER STEERING Capacity: 1,1 liter		
use Normal	climate Moderate	
PRODUCT RECOMMENDATION 1 ATF Dexron II-D		

Check every 50 hours, change every 300 hours

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

COOLING SYSTEM Capacity: 6,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
	10 1	

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.