## **ISEKI TM TM 217 F** (1995 AND AFTER)



ENGINE E3100 Capacity: 2,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	

Check every 10 hours, change every 150 hours

use Normal	
SP Gear 5015	Gearlube GL-4 80W

Check every 50 hours, change every 300 hours

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING Capacity: 13,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Kroontrak MTH 10W-30	Agrifluid HT		

Check every 10 hours, change every 200 hours

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Check every 50 hours			

COOLING SYSTEM Capacity: 5,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Chaok ayan, E0 hayra ahanga ayan	12	<u>'</u>

Check every 50 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

## PRODUCT RECOMMENDATION

## **ISEKI TM TM 217 F** (1995 AND AFTER)



information contained herein is subject to changes without notification.